


PRODUCT IMAGE / IMAGE DU PRODUIT



GENERAL SPECIFICATIONS / SPECIFICATION GÉNÉRALES

Designation IEC / Désignation IEC	6AM6 / 9V Block
Technology / Technologie	Lithium/Iron Disulfide
Chemical system / Système chimique	Li/FeS ₂
Nominal voltage / Tension nominale	9V
Capacity (mAh)	1150
<i>*1mA, 24h/day at 20+/-2°C, EPV 5.4V</i>	
Max Discharge Current / Courant de décharge maximum	120 mA
Discharge Cut-off Voltage / Tension de coupure de décharge	5.4V
Average weight (g) / Poids moyen (g)	45g
Shelf Life / Durée de vie	> 10 years / 10 ans
Mercury & Cadmium Free	100%

TEMPERATURE RANGE / PLAGE DE TEMPÉRATURE

Operating temperature range / Température d'utilisation	-40°C to +60°C
Storage Temperature Range / Température de stockage	-20°C to +40°C

RECOMMENDED APPLICATIONS / APPLICATIONS RECOMMANDÉES

Smoke detector Toy Radio Microphone	Détecteur de fumée Jouet Radio Microphone
--	--

PERFORMANCE CHARACTERISTICS / CARACTÉRISTIQUES DE PERFORMANCE

Applications / Applications	N/A	N/A	
Load / Charge	115mA	1mA	
Discharge Mode / Mode de décharge	1h/d	1h/d	
End Voltage / Tension de fin	5.4V	5.4V	
Normal Duration / Durée normale	7	1250	
Unit / Unité	Hr	Hr	

*The above information is generally descriptive only and is not intended as guarantee or warranty
 **Uniross reserves the right to alter or amend the design, model and specification without prior notice.