

PRODUCT IMAGE / IMAGE DU PRODUIT




GENERAL SPECIFICATIONS / SPECIFICATION GÉNÉRALES

Classification/ Classification	Nickel Metal Hydride
Battery Type / Type de Batteries	AA
Nominal voltage / Tension Nominale	1.2V
Nominal capacity / Capacité Nominale	2500mAh
Minimal capacity / Capacité Minimale	2350mAh
Weight / Poids	29.5 g

CHARGING INFORMATION / INFORMATION SUR LA CHARGE


Standard Charge Charge Standard	235mA×16h
Rapid Charge Charge Rapide	5-10mV
Internal Impedance Impédance Interne	< 35 mΩ after standard charge at 1 kHz for 1 hour
Cycle Life Cycle de Vie	> 350
Max Continuous Discharge Current Courant Maximal de Charge	4700mA

DIMENSIONS




D	14.5 ⁺⁰ _{-0.7} mm
H	50.5 ⁺⁰ _{-1.5} mm
D ¹	5.4 ⁺⁰ _{-0.2} mm
H ¹	1.3 ^{+0.2} mm

DISCHARGE CHARACTERISTICS



CHARGE CHARACTERISTICS



AMBIENT TEMPERATURE RANGE / PLAGE DE TEMPERATURE AMBIANTE

Operating temperature range for humidity: +65%± 20% Température d'utilisation avec une humidité de 65%± 20%	Standard charge / Charge Standard Floating charge / Charge Flottante Rapid charge / Rapide Charge Discharge / Décharge	0 to +45°C (32 to 113°F) +10 to +45°C (50 to 113°F) -10 to +45°C (14 to 113°F) -20 to +65°C (-4 to 149°F)
Storage temperature range for humidity: +65%±20% Température de stockage avec une humidité de 65%± 20%	Within 1 year / Première année Within 6 months / Premiers mois Within 1month: / Premier mois Within 1 week / Première semaine	-20 to +35°C (-4 to 95°F) -20 to +45°C (-4 to 113°F) -20 to +55°C (-4 to 131°F) -20 to +65°C (-4 to 149°F)
Discharge at low Temperature Décharge à basse température	> 210 min at 0°C±2°C with 0.2C mA, after stored at 0°C±2°C for 24 hours	
Self Discharge / Auto-décharge	> 80% from rated capacity at 0.2C mA, after stored for 6 months > 70% from rated capacity at 0.2C mA, after stored for 12 months	
Humidity for operation and storage Humidité pour utilisation et stockage	65%±20%	

*The above information is generally descriptive only and is not intended as guarantee or warranty

**Uniross reserves the right to alter or amend the design, model and specification without prior notice.