

PRODUCT IMAGE / IMAGE DU PRODUIT


Input Power / Tension d 'Entrée	100 ~ 240VCA / 50~60Hz
Output Power / Tension de Sortie	19.5VDC
Max. Output Current / Courant de Sortie Max.	2.3A
Max. Output Power / Puissance de Sortie Max.	45W
Ripple / Ondulation	300p-p max.
Cable length / Longueur du câble	1.5m
Dimensions Lx W X H (mm)	86 x 51 x 32
Weight / Poids	166.5g

7 ADAPTER PLUGS INCLUDED / 7 ADAPTEURS INCLUS

AG	12.0 x 4.5mm pin:0.6mm
AH	11mm Square
QV2	12.5 x 7.4mm, Pin 0.6mm
g	9.0 x 2.5mm, Pin 0.7mm
R	12.0 x 5.5mm, Pin 1.7mm
V	11.5 x 4.0mm, Pin 1.7mm
AA	8.0 x 3.0mm, Pin 1.0mm

SAFETY FEATURES / DISPOSITIFS DE SÉCURITÉ

Short circuit Protection / Protection contre les courts circuits	✓
Over Current Protection / Protection contre les surtensions	✓
Over Voltage Protection / Protection contre les surcharges	✓
Over Temperature Protection / Protection contre surchauffe	✓

OTHER INFORMATION / AUTRES INFORMATIONS

Compatibility	<p>AG Tip -> HP Pavillon, Elitebook, Probook Series</p> <p>AH Tip -> Lenovo Yoga 2 11 11s 13, Yoga 2 Pro, IdeaPad 500 S210 U430 U530, Flex 2 3 15 15D 14 10, Thinkpad Edge E431, E531</p> <p>QV2 Tip -> HP Compaq 6000, 8000 Series</p> <p>g Tip -> Asus Eee PC</p> <p>R Tip -> Acer Aspire One</p> <p>V Tip -> HP mini Notebook</p> <p>AA Tip -> Asus Zenbook, Samsung O Series</p>
Warranty / Garantie	2 Years / 2 Ans
Standards	EN 60950-1 EN 55022/4 EN 61000-3-2/3 RoHS Directive 2011/65/EC ErP Directive 2009/125/EC
Available Versions / Versions Disponible	EU / UK
Packing Information / Information Emballage	Inner: 10pcs / Outer: 20pcs