

PRODUCT IMAGE / IMAGE DU PRODUIT


Input Power / Tension d 'Entrée	100 ~ 240VCA / 50~60Hz
Output Power / Tension de Sortie	19VDC
Max. Output Current / Courant de Sortie Max.	4.73A
Max. Output Power / Puissance de Sortie Max.	65W
Ripple / Ondulation	400p-p max.
Cable length / Longueur du câble	1.2m
Dimensions Lx W X H (mm)	138 x 66 x 25
Weight / Poids	320g

7 ADAPTER PLUGS INCLUDED / 7 ADAPTEURS INCLUS

AG	12.0 x 4.5mm pin:0.6mm
AH	11mm Square
P	12.0 x 5.5mm, Pin 2.5mm
N	11.5 x 7.9mm, Pin 0.9mm
QV2	12.5 x 7.4mm, Pin 0.6mm
T	10.0 x 4.75mm, Pin 1.7mm
X	12.0 x 5.5mm, Pin 1.7mm

SAFETY FEATURES / DISPOSITIFS DE SÉCURITÉ

Short circuit Protection / Protection contre les courts circuits	✓
Over Current Protection / Protection contre les surtensions	✓
Over Voltage Protection / Protection contre les surcharges	✓
Over Temperature Protection / Protection contre surchauffe	✓

OTHER INFORMATION / AUTRES INFORMATIONS

Compatibility	<p>AG Tip -> HP Pavillon, Elitebook, Probook Series</p> <p>AH Tip -> Lenovo Yoga 2 11 11s 13, Yoga 2 Pro, IdeaPad 500 S210 U430 U530, Flex 2 3 15 15D 14 10, Thinkpad Edge E431, E531</p> <p>P Tip -> Asus, HP, Compaq, Fujitsu, NEC, Packard Bell, Sharp, Toshiba, MSI, LG, Gateway</p> <p>N Tip -> ThinkPad T W Series</p> <p>QV2 Tip -> HP Compaq 6000, 8000 Series</p> <p>T Tip -> HP Pavillon Series</p> <p>X Tip -> Acer Aspire Timeline, Timeline Ultra Series</p>
Warranty / Garantie	2 Years / 2 Ans
Standards	EN 60950-1 EN 55022/4 EN 61000-3-2/3 RoHS Directive 2011/65/EC ErP Directive 2009/125/EC
Available Versions / Versions Disponible	EU / UK
Packing Information / Information Emballage	Inner: 10pcs / Outer: 20pcs